


TOSHIBA GTR MODULE SILICON N CHANNEL IGBT

# MG360V1US41

HIGH POWER SWITCHING APPLICATIONS.  
MOTOR CONTROL APPLICATIONS.

EQUIVALENT CIRCUIT



- The Electrodes are Isolated from Case.
- High Input Impedance
- Enhancement-Mode
- High Speed :  $t_f = 1.5\mu s$  (Max.) ( $I_C = 360A$ )  
 $t_{rr} = 0.6\mu s$  (Max.) ( $I_F = 360A$ )
- Outline : TOSHIBA 2-109E1A  
(See page 3 for the device outline)
- Weight : 590g (TYP.)

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Emitter Voltage	$V_{CES}$	1700	V
Gate-Emitter Voltage	$V_{GES}$	$\pm 20$	V
Collector Current	DC	$I_C$	A
	1ms	$I_{CP}$	
Forward Current	DC	$I_F$	A
	1ms	$I_{FM}$	
Collector Power Dissipation (Tc = 25°C)	$P_C$	3600	W
Junction Temperature	$T_j$	150	°C
Storage Temperature Range	$T_{stg}$	-40~125	°C
Isolation Voltage	$V_{Isol}$	4000 (AC 1 min.)	V
Screw Torque (M4 / M6 / Mounting)	—	2 / 3 / 3	N · m


961001EAA2

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

ELECTRICAL CHARACTERISTICS (Ta = 25°C)


CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Gate Leakage Current		$I_{GES}$	$V_{GE} = \pm 20V, V_{CE} = 0$	—	—	$\pm 300$	nA
Collector Cut-off Current		$I_{CES}$	$V_{CE} = 1700V, V_{GE} = 0$	—	—	6.0	mA
Gate-Emitter Cut-off Voltage		$V_{GE(off)}$	$I_C = 360mA, V_{CE} = 5V$	4.0	—	8.0	V
Collector-Emitter Saturation Voltage		$V_{CE(sat)}$	$I_C = 360A, V_{GE} = 15V$	—	3.2	4.5	V
Input Capacitance		$C_{ies}$	$V_{CE} = 10V, V_{GE} = 0,$ $f = 1MHz$	—	49200	—	pF
Switching Time	Turn-on Delay Time	$t_{d(on)}$	Inductive Load $V_{CC} = 900V$ $I_C = 360A$ $V_{GE} = \pm 15V$ $R_G = 2.0\Omega$ (Note 1)	—	0.1	—	$\mu S$
	Rise Time	$t_r$		—	0.1	—	
	Turn-on Time	$t_{on}$		—	0.5	—	
	Turn-off Delay Time	$t_{d(off)}$		—	0.4	—	
	Fall Time	$t_f$		—	0.5	1.5	
	Turn-off Time	$t_{off}$		—	1.0	—	
Forward Voltage		$V_F$	$I_F = 360A, V_{GE} = 0$	—	3.7	5.0	V
Reverse Recovery Time		$t_{rr}$	$I_F = 360A, V_{GE} = -15V$ $di/dt = 1000A/\mu S$ (Note 1)	—	0.3	0.6	$\mu S$
Thermal Resistance		$R_{th(j-c)}$	Transistor Stage	—	—	0.035	$^{\circ}C/W$
			Diode Stage	—	—	0.125	

Note 1 Switching Time and Reverse Recovery Time Test Circuit & Timing Chart



OUTLINE : TOSHIBA 2-109E1A

Unit in mm



Weight : 590g (TYP.)

